



**ISOTOP® Boost chopper
MOSFET Power Module**

$$V_{DSS} = 500V$$

$$R_{DSon} = 100m\Omega \text{ max @ } T_j = 25^\circ C$$

$$I_D = 44A \text{ @ } T_c = 25^\circ C$$



Application

- AC and DC motor control
- Switched Mode Power Supplies
- Power Factor Correction
- Brake switch

Features

- Power MOS V[®] MOSFETs
 - Low R_{DSon}
 - Low input and Miller capacitance
 - Low gate charge
 - Fast intrinsic diode
 - Avalanche energy rated
 - Very rugged
- ISOTOP® Package (SOT-227)
- Very low stray inductance
- High level of integration

Benefits

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Very rugged
- Low profile

Absolute maximum ratings

Symbol	Parameter			Max ratings	Unit
V _{DSS}	Drain - Source Breakdown Voltage			500	V
I _D	Continuous Drain Current	T _c = 25°C		44	A
		T _c = 80°C		33	
I _{DM}	Pulsed Drain current			176	
V _{GS}	Gate - Source Voltage			±30	V
R _{DSon}	Drain - Source ON Resistance			100	mΩ
P _D	Maximum Power Dissipation	T _c = 25°C		450	W
I _{AR}	Avalanche current (repetitive and non repetitive)			44	A
E _{AR}	Repetitive Avalanche Energy			50	mJ
E _{AS}	Single Pulse Avalanche Energy			2500	
IF _{AV}	Maximum Average Forward Current	Duty cycle=0.5	Tc = 80°C	30	A
IF _{RMS}	RMS Forward Current (Square wave, 50% duty)			39	

CAUTION: These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.

All ratings @ $T_j = 25^\circ\text{C}$ unless otherwise specified

Electrical Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
BV_{DSS}	Drain - Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu A$	500			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{GS} = 0V, V_{DS} = 500V, T_j = 25^\circ\text{C}$			25	μA
		$V_{GS} = 0V, V_{DS} = 400V, T_j = 125^\circ\text{C}$			250	
$R_{DS(on)}$	Drain - Source on Resistance	$V_{GS} = 10V, I_D = 22A$			100	$m\Omega$
$V_{GS(th)}$	Gate Threshold Voltage	$V_{GS} = V_{DS}, I_D = 2.5mA$	2		4	V
I_{GSS}	Gate - Source Leakage Current	$V_{GS} = \pm 20V, V_{DS} = 0V$			± 100	nA

Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C_{iss}	Input Capacitance	$V_{GS} = 0V$		7410		pF
C_{oss}	Output Capacitance	$V_{DS} = 25V$		1050		
C_{rss}	Reverse Transfer Capacitance	$f = 1MHz$		390		
Q_g	Total gate Charge	$V_{GS} = 10V$		312		nC
Q_{gs}	Gate - Source Charge	$V_{Bus} = 250V$		37		
Q_{gd}	Gate - Drain Charge	$I_D = 44A @ T_j = 25^\circ\text{C}$		127		
$T_{d(on)}$	Turn-on Delay Time	$V_{GS} = 15V$		18		ns
T_r	Rise Time	$V_{Bus} = 250V$		16		
$T_{d(off)}$	Turn-off Delay Time	$I_D = 44A @ T_j = 25^\circ\text{C}$		54		
T_f	Fall Time	$R_G = 0.6\Omega$		5		


Diode ratings and characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
V_F	Diode Forward Voltage	$I_F = 30A$		1.6	1.8	V
		$I_F = 60A$		1.9		
		$I_F = 30A, T_j = 125^\circ\text{C}$		1.4		
I_{RM}	Maximum Reverse Leakage Current	$V_R = 600V, T_j = 25^\circ\text{C}$			250	μA
		$V_R = 600V, T_j = 125^\circ\text{C}$			500	
C_T	Junction Capacitance	$V_R = 200V$		44		pF
t_{rr}	Reverse Recovery Time	$I_F = 1A, V_R = 30V, di/dt = 100A/\mu s, T_j = 25^\circ\text{C}$		23		ns
	Reverse Recovery Time	$T_j = 25^\circ\text{C}$		85		
		$T_j = 125^\circ\text{C}$		160		
I_{RRM}	Maximum Reverse Recovery Current	$I_F = 30A, V_R = 400V, di/dt = 200A/\mu s, T_j = 25^\circ\text{C}$		4		A
		$T_j = 125^\circ\text{C}$		8		
		$T_j = 25^\circ\text{C}$		130		
Q_{rr}	Reverse Recovery Charge	$T_j = 125^\circ\text{C}$		700		nC
t_{rr}	Reverse Recovery Time	$I_F = 30A, V_R = 400V, di/dt = 1000A/\mu s, T_j = 125^\circ\text{C}$		70		ns
Q_{rr}	Reverse Recovery Charge			1300		nC
I_{RRM}	Maximum Reverse Recovery Current			30		A

Thermal and package characteristics

Symbol	Characteristic		Min	Typ	Max	Unit
R_{thJC}	Junction to Case	MOSFET			0.28	°C/W
		Diode			1.21	
R_{thJA}	Junction to Ambient (IGBT & Diode)				20	
V_{ISOL}	RMS Isolation Voltage, any terminal to case $t = 1$ min, $I_{isol} < 1$ mA, 50/60Hz		2500			V
T_J, T_{STG}	Storage Temperature Range		-55		150	°C
T_L	Max Lead Temp for Soldering: 0.063" from case for 10 sec				300	
Torque	Mounting torque (Mounting = 8-32 or 4mm Machine and terminals = 4mm Machine)				1.5	N.m
Wt	Package Weight			29.2		g

Typical MOSFET Performance Curve






FIGURE 2, TYPICAL OUTPUT CHARACTERISTICS




FIGURE 3, TYPICAL OUTPUT CHARACTERISTICS




FIGURE 4, TYPICAL TRANSFER CHARACTERISTICS




FIGURE 5, $R_{DS(ON)}$ vs DRAIN CURRENT




FIGURE 6, MAXIMUM DRAIN CURRENT vs CASE TEMPERATURE




FIGURE 7, BREAKDOWN VOLTAGE vs TEMPERATURE




FIGURE 8, ON-RESISTANCE vs. TEMPERATURE




FIGURE 9, THRESHOLD VOLTAGE vs TEMPERATURE




FIGURE 10, MAXIMUM SAFE OPERATING AREA




FIGURE 11, TYPICAL CAPACITANCE vs DRAIN-TO-SOURCE VOLTAGE




FIGURE 12, GATE CHARGES vs GATE-TO-SOURCE VOLTAGE




FIGURE 13, TYPICAL SOURCE-DRAIN DIODE FORWARD VOLTAGE

Typical Diode Performance Curve




FIGURE 1a. MAXIMUM EFFECTIVE TRANSIENT THERMAL IMPEDANCE, JUNCTION-TO-CASE vs. PULSE DURATION




FIGURE 1b, TRANSIENT THERMAL IMPEDANCE MODEL




Figure 2. Forward Current vs. Forward Voltage




Figure 3. Reverse Recovery Time vs. Current Rate of Change




Figure 4. Reverse Recovery Charge vs. Current Rate of Change




Figure 5. Reverse Recovery Current vs. Current Rate of Change




Figure 6. Dynamic Parameters vs. Junction Temperature




Figure 7. Maximum Average Forward Current vs. Case Temperature




Figure 8. Junction Capacitance vs. Reverse Voltage




Figure 9. Diode Test Circuit





Figure 10. Diode Reverse Recovery Waveform and Definitions

SOT-227 (ISOTOP®) Package Outline



ISOTOP® is a Registered Trademark of SGS Thomson

APT reserves the right to change, without notice, the specifications and information contained herein

APT's products are covered by one or more of U.S. patents 4,895,810 5,045,903 5,089,434 5,182,234 5,019,522 5,262,336 6,503,786 5,256,583 4,748,103 5,283,202 5,231,474 5,434,095 5,528,058 and foreign patents. U.S. and Foreign patents pending. All Rights Reserved.