

80143

1.0 Watts, 15 Volts, Class A
Linear to 2300 MHz

GENERAL DESCRIPTION

The 80143 is a COMMON EMITTER transistor capable of providing 1.0 Watts of Class A, RF output power to 2300 MHz. This transistor is specifically designed for general Class A amplifier applications. It utilizes gold metalization and diffused ballasting to provide high reliability and supreme ruggedness. The transistor uses a fully hermetic High Temperature Solder Sealed package.

ABSOLUTE MAXIMUM RATINGS

Maximum Power Dissipation @ 25°C 4.5 Watts


Maximum Voltage and Current

BVces	Collector to Emitter Voltage	50 Volts
BVebo	Emitter to Base Voltage	3.5 Volts
Ic	Collector Current	0.6 Amps

Maximum Temperatures

Storage Temperature	- 65 to + 200°C
Operating Junction Temperature	+ 200°C

CASE OUTLINE 55BT, STYLE 2



ELECTRICAL CHARACTERISTICS @ 25 °C

SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Pout	Power Out	F = 2.3 GHz	1.0			Watts
Pin	Power Input	Ic = 200 mA			0.125	Watts
Pg	Power Gain	Vcc = 15 Volts	9.0	10.0		dB
Ft	Transition Frequency	Vce = 15V, Ic = 200 mA	4.2	4.5		GHz
VSWR	Load Mismatch Tolerance				10:1	


BVebo	Emitter to Base Breakdown	Ie = 2 mA	3.5			Volts
BVces	Collector to Emitter Breakdown	Ic = 20 mA	50			Volts
BVceo	Collector to Emitter Breakdown	Ic = 20 mA	20			Volts
hFE	DC Current Gain	Vce = 5 V, Ic = 200 mA	20			
Cob	Capacitance	Vcb = 28V, f = 1 MHz		3.4		pF
θjc	Thermal Resistance				30	°C/W

Initial Issue June, 1994

GHz TECHNOLOGY INC. RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. GHz RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.


POWER OUTPUT vs FREQUENCY

$V_{cc}=15V$




POWER OUTPUT vs POWER INPUT

$V_{ce}=12,15,18 \text{ Volts}; I_c=200mA$



DC SAFE OPERATING AREA




MMICAD for Windows Fri Aug 26 16:33:49 1994

CIRCUIT: MES

FREQ	--- S11 ---		--- S21 ---		--- S12 ---		--- S22 ---	
MHz	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.100	0.74523	-139.072	23.1569	122.888	0.02130	38.6374	0.63665	-59.3430
0.200	0.83904	-160.387	13.2482	102.204	0.02481	21.9060	0.41262	-79.9929
0.300	0.86349	-169.532	9.16285	88.7446	0.02580	16.4347	0.33897	-90.5201
0.400	0.86945	-175.151	6.95469	80.6123	0.02656	14.7851	0.31507	-97.6573
0.500	0.87126	-179.220	5.58335	74.7734	0.02687	14.2935	0.31273	-103.182
0.600	0.87258	177.456	4.65226	68.6924	0.02714	13.6292	0.32109	-107.892
0.700	0.87336	174.600	3.98221	61.9474	0.02780	13.7272	0.33588	-112.258
0.800	0.87406	172.167	3.47879	56.5060	0.02858	14.7467	0.35353	-116.149
0.900	0.87451	169.727	3.09034	51.3262	0.02910	14.9821	0.37354	-119.802
1.000	0.87453	167.348	2.78319	46.4507	0.02988	15.5773	0.39486	-123.289
1.100	0.87250	165.042	2.52784	41.6152	0.03071	15.8776	0.41654	-126.688
1.200	0.87116	162.788	2.31762	36.8549	0.03160	15.8605	0.43867	-129.991
1.300	0.86967	160.535	2.13966	32.1575	0.03283	16.4435	0.45927	-133.270
1.400	0.86986	158.314	1.98768	27.4928	0.03400	16.6297	0.47936	-136.529
1.500	0.86824	155.918	1.85641	22.8336	0.03539	17.2656	0.49878	-139.661
1.600	0.86604	153.421	1.74081	18.2254	0.03715	17.0624	0.51780	-142.847
1.700	0.86184	150.901	1.63766	13.6683	0.03858	17.1415	0.53552	-145.989
1.800	0.85937	148.379	1.54533	9.18261	0.04023	16.2272	0.55225	-149.096
1.900	0.85612	145.720	1.46274	4.78123	0.04221	16.4217	0.56783	-152.155
2.000	0.85458	143.071	1.39093	0.39241	0.04425	15.7298	0.58247	-155.087
2.100	0.85286	140.202	1.32681	-4.05113	0.04756	14.6697	0.59834	-158.056
2.200	0.84763	137.149	1.26508	-8.50524	0.04983	12.8878	0.61184	-161.166
2.300	0.84009	133.993	1.20767	-12.7453	0.05193	10.6982	0.62395	-163.961
2.400	0.83220	131.013	1.15845	-16.8963	0.05368	8.83368	0.63750	-166.655
2.500	0.82465	128.048	1.11640	-20.9442	0.05551	7.95492	0.65178	-169.272
2.600	0.82067	124.938	1.07896	-25.1542	0.05751	6.83706	0.66487	-172.024
2.700	0.81483	121.427	1.04441	-29.3750	0.06047	5.84021	0.67664	-174.598
2.800	0.80880	117.847	1.01308	-33.6115	0.06346	4.53989	0.68926	-177.140
2.900	0.79979	114.017	0.98350	-37.9183	0.06665	2.84239	0.70128	-179.771
3.000	0.79177	110.076	0.95667	-42.2425	0.07059	1.12060	0.71196	177.606


REVISIONS

ZONE	REV	DESCRIPTION	DATE	APPROVED
------	-----	-------------	------	----------



DIM	INCHES
A	.430
B	.430
C	.055
D	.800
E	.300
F	.485
G	.085
H	.085
I	.120
J	.565
K	.270
L	.620
M	.315
N	.700
O	.085
P	.155
Q	.200

80143 TEST CIRCUIT
2.3 GHz



$C_a = C_b = 82\text{pF}$ ATC CASE A
MICROSTRIP=TEFLON FIBERGLASS BOARD
 $h = .030"$ $E_r = 2.55$

$C1 = 0.1\mu\text{F}$ $Q1 = 2N1907$
 $C2, C3 = 82\text{pF}$
 $R1 = 1.8\text{K}\Omega$
 $R2 = 10\text{K}\Omega$
 $R3 = 9.1\Omega$
 $R4 = 200\Omega$
 $\text{RFC} = L1 = L2 = 6 \text{ turns } \#20 \text{ AWG } 0.060 \text{ dia}$



CAGE OPJR2	DWG NO. 80143	REV A
SCALE 1/1	SHEET	