

RSC120HF120A2N

SiC MOSFET Module

Preliminary Data


Features:

- Ultra Low Loss
- High-Frequency Operation
- Zero Reverse Recovery Current from Diode
- Zero Turn-off Tail Current from MOSFET
- Normally-off, Fail-safe Device Operation
- Easy of Paralleling
- Copper Baseplate and Aluminum Nitride Insulator



Applications:

- Induction Heating
- DC/DC Converters
- Solar and Wind Inverters
- Line Regen Drives
- Battery Charge



Absolute Maximum Ratings ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Description		Value	Units
V_{DSmax}	Drain-Source Voltage		1200	V
V_{GSmax}	Gate-Source Voltage	Absolute Maximum values	-10/+25	V
V_{GSop}	Gate-Source Voltage	Recommended Operational Values	-5/20	V
I_D	Continuous Drain Current	$V_{GS}=20\text{V}, T_C=25^\circ\text{C}$	193	A
		$V_{GS}=20\text{V}, T_C=90^\circ\text{C}$	138	A
$I_{D(pluse)}$	Pulsed Drain Current	Pulse width t_p limited by T_{jmax}	480	A
P_D	Power Dissipation	$T_C=25^\circ\text{C}, T_J=150^\circ\text{C}$	925	W

Electrical Characteristics of MOSFET ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Description	Conditions	Min	Typ	Max	Unit
$V_{(BR)DSS}$	Drain - Source Breakdown Voltage	$V_{GS}=0V, I_D=300\mu A$	1.2			V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = 10\text{ V}, I_D = 6\text{ mA}$	1.8	2.6		V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 1.2\text{ kV}, V_{GS} = 0V$		80	300	μA
		$V_{DS} = 1.2\text{ kV}, V_{GS} = 0V,$ $T_J = 150^\circ\text{C}$		400	1500	μA
I_{GSS}	Gate-Source Leakage Current	$V_{GS} = 20\text{ V}, V_{DS} = 0V$		1	100	nA
$R_{DS(on)}$	On State Resistance	$V_{GS} = 20\text{ V}, I_{DS} = 120\text{ A}$		13	16	m Ω
		$V_{GS} = 20\text{ V}, I_{DS} = 120\text{ A},$ $T_J = 150^\circ\text{C}$		23	30	
g_{fs}	Transconductance	$V_{DS} = 20\text{ V}, I_{DS} = 120\text{ A}$		53.8		S
		$V_{DS} = 20\text{ V}, I_{DS} = 120\text{ A}, T_J=150^\circ\text{C}$		48.5		
C_{iss}	Input Capacitance	$V_{DS} = 1KV, f = 200\text{ kHz},$ $V_{AC} = 25\text{ mV}$		6.3		nF
C_{oss}	Output Capacitance			0.88		
C_{rss}	Reverse Transfer Capacitance			0.037		
E_{on}	Turn-On Switching Energy	$V_{DD} = 600\text{ V}, V_{GS} = -5V/+20V$ $I_D = 120\text{ A}, R_{G(ext)} = 2.5\ \Omega$		1.7		mJ
E_{off}	Turn-Off Switching Energy			0.4		
$R_{G(int)}$	Internal Gate Resistance	$f = 200\text{ kHz}, V_{AC} = 25\text{ mV}$		1.8		Ω
Q_{GS}	Gate-Source Charge	$V_{DD}= 800\text{ V}, V_{GS} = -5V/+20V,$ $I_D= 120\text{ A},$		97		nC
Q_{GD}	Gate-Drain Charge			118		
Q_G	Total Gate Charge			378		
$t_{d(on)}$	Turn-off delay time	$V_{DD} = 600V, V_{GS} = -5/+20V,$ $I_D = 120\text{ A}, R_{G(ext)} = 2.5\ \Omega,$		38		ns
t_r	Rise Time			34		
$t_{d(off)}$	Turn-off delay time			70		
t_f	Fall Time			22		
$R_{\theta JCM}$	Thermal Resistance Junction-To-Case for MOSFET			0.125	0.135	$^\circ\text{C}/\text{W}$

Free-Wheeling SiC Schottky Diode Characteristics ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Description	Conditions	Min	Typ	Max	Unit
V_{SD}	Diode Forward Voltage	$I_F = 120\text{ A}, V_{GS} = 0$		1.5	1.8	V
		$I_F = 120\text{ A}, V_{GS} = 0, T_J=150^\circ\text{C}$		1.9	2.4	
Q_C	Total Capacitive Charge	$I_{SD} = 120\text{ A}, V_{DS} = 600\text{ V}, T_J = 25^\circ\text{C}, di_{SD}/dt = 3\text{ kA}/\mu\text{s}, V_{GS} = -5\text{ V}$		1.1		μC
$R_{\theta JCD}$	Thermal Resistance Junction-To-Case for Diode			0.108	0.115	$^\circ\text{C}/\text{W}$
I_F	Continuous Diode Forward Current	$V_{GS} = -5\text{ V}, T_C=25^\circ\text{C}$			305	A
		$V_{GS} = 5\text{ V}, T_C=25^\circ\text{C}$			195	A

Module

Symbol	Description	Conditions	Min	Typ	Max	Unit
T_{Jmax}	Junction Temperature		-40		150	$^\circ\text{C}$
T_C, T_{STG}	Case and Storage Temperature Range		-40		125	$^\circ\text{C}$
V_{isol}	Case Isolation Voltage	AC, 50 HZ, 1 min	5.0			KV
L_{Stray}	Stray Inductance	Measured between terminals 2 and 3			15	nH
G	Weight			300		g
M	Mounting Torque	To heatsink and terminal			5	N·m
	Clearance Distance	Terminal to terminal			12	mm
	Creepage Distance	Terminal to terminal			30	mm
		Terminal to baseplate			40	mm




Fig.1 Output Characteristic $T_j = -40^\circ\text{C}$




Fig.2 Output Characteristics $T_j = 25^\circ\text{C}$




Fig.3 Output Characteristic $T_j = 150^\circ\text{C}$




Fig.4 Normalized On-Resistant VS Temperature




Fig.5 On-Resistant VS Drain Current For Various Temperatures




Fig.6 On-Resistant vs Temperatures For Various Gate-Source voltage




Fig.7 Threshold Voltage VS Temperature




Fig.8 Transfer Characteristic for Various Junction Temperature




Fig.9 Diode Characteristic at -40°C




Fig.10 Diode Characteristic at 25°C




Fig.11 Diode Characteristic at 150°C




Fig.12 3rd Quadrant Characteristic at -40°C




Fig.13 3rd Quadrant Characteristic at 25°C




Fig.14 3rd Quadrant Characteristic at 150°C




Fig.15 Typical Gate Charge Characteristic




Fig.16 Capacitances VS Drain-Source Voltage (0-200V)




Fig.17 Typical Capacitances VS Drain-Source Voltage (0-1KV)




Fig.18 Typical Output Capacitor Stored Energy




Fig.19 Inductive Switching Energy VS Drain Current For $V_{DS}=600A, R_G=2.5 \Omega$




Fig.20 Inductive Switching Energy VS Drain Current For $V_{DS}=800A, R_G=2.5 \Omega$




Fig.21 Inductive Switching Energy VS $R_{G(ext)}$




Fig.22 Inductive Switching Energy VS Temperature




Fig.23 Maximum Power Dissipation (MOSFET) Derating VS Case Temperature




Fig.24 Continuous Drain Current Derating VS Case Temperature




Fig.25 Timing VS $R_{G(ext)}$




Fig.26 Resistive Switching Time Description




Fig.27 MOSFET Junction Case Thermal Impedance




Fig.28 Diode Junction to Case Thermal Impedance






Fig.29 Maximum Power Dissipation (MOSFET) Derating Vs. Case Temperature

Internal Circuit



Package Outline (Unit: mm):



View A
scale 3:1

